

SCREEN PRINTING CHEMICALS

ER-125

Emulsion Remover Concentrate With Degreasers

DESCRIPTION

ER-125 is a concentrated Emulsion Remover formulation designed for fast removal of emulsions and capillary films from screens by means of spray or wipe-on application. ER-125 has degreasers built in to eliminate additional steps in the reclamation process.

ADVANTAGES

- ❖ Fast removal of hardened emulsions
- ❖ Ecologically sound
- ❖ Drain Safe
- ❖ Concentrated for maximum economy

DIRECTIONS

This container of ER-125 can be diluted from 1:2 to 1:5 (chemical:water) depending on emulsion type and method of application. After determining proper ratio for your needs, mix contents in plastic container and fill with appropriate amount of water.

Spray on ER-125 in a uniform pattern onto the print contact side of the screen. In some cases better results are obtained by applying ER-125 onto both sides of the screen. Allow to stand up to 3 minutes depending on the type and hardness of the emulsion. Remove the emulsion using a medium to high pressure cold water rinse. Flush the screen with a final rinse to remove any trace chemicals left on the screen. Allow to dry completely before recoating.

TYPICAL PRODUCT PROPERTIES

Appearance	Clear, colorless liquid
Odor	Unscented
pH	3.5
Flash Point	None
Specific Gravity	1.10
Stability	Stable



6690 Jones Mill Court • Buildings A&B • Norcross, Georgia 30092 USA
 Phone 770.441.5900 • Fax 770.409.7259 • Toll Free 1.800.241.7708
 e-mail: anc@mindspring.com • Website: www.american-niagara.com