

SCREEN PRINTING CHEMICALS

ER-188

Full Strength Emulsion Remover

DESCRIPTION

ER-188 is a full strength emulsion remover designed for fast removal of emulsions and capillary films from screens.

ADVANTAGES

- Fast removal of hardened emulsions
- Economical
- Ecologically sound
- Drain Safe

DIRECTIONS

Before using, clean the ink from the screen with non film forming ink remover such as Bio-2. As a good pre-rinse step, rinse the screen with water to remove any block-out. Spray on ER-188 in a uniform pattern onto the print contact side of the screen. In some cases better results are obtained by applying ER-188 onto both sides of the screen. Allow to stand up to 3 minutes depending on the type and hardness of the emulsion. Remove the emulsion using a medium to high pressure cold water rinse. Flush the screen with a final rinse to remove any trace chemicals left on the screen. Allow to dry completely before recoating.

TYPICAL PRODUCT PROPERTIES

AppearanceClear, colorless liquid
Odor Unscented
pH 4.5
Flash Point None
Specific Gravity 1.02
Stability Stable



6690 Jones Mill Court • Buildings A&B • Norcross, Georgia 30092 USA Phone 770.441.5900 • Fax 770.409.7259 • Toll Free 1.800.241.7708 e-mail: anc@mindspring.com • Website: www.american-niagara.com